



SEMIN AIRLESS

3 in 1

3 ACTIONS : UNDERLAYER - FILLER - FINISH

TECHNICAL DEFINITION

SEMIN AIRLESS 3 in 1 is an interior filler that can be used as an Airless spray.

It provides an even appearance without smoothing, has great coverage and a deep matt finish.

It combines 3 actions: underlayer, filler and finish.

COMPOSITION AND APPEARANCE

Acrylic emulsion resin, mineral content, cellulose derivatives, preservation agent and other additives.

The resulting paste is a bright white colour and its consistency is adapted to its airless application.

ACCEPTABLE SURFACES SEMIN AIRLESS 3 IN 1 is sprayed onto plaster boards that have been carefully grouted, reviewed and dusted, or to any other smooth surface.

COVERING

The SEMIN AIRLESS 3 in 1 layers can be applied with an acrylic or gloss paint.

REFERENCE DOCUMENTS

DTU 59.1.

TECHNICAL CHARACTERISTICS

- Dry extract: 68 %.
- Density: 1.76
- COV: < 1g/l.

PACKING

25 kg pails.

STORAGE

18 months, away from frost, in original unopened packaging.

APPLICATION

PRECAUTIONS DURING USE

The temperature for application and during drying must be between 8 and 35° C. Do not apply on frozen substrates.

SURFACE PREPARATION

Surfaces must conform to DTU 59.1

i.e., they must be dry, clean, hard, without any traces of the parting agent...

DRYING TIME

6 to 24 hours depending on the amount applied

QUANTITY

1.2 to 1.5 kg/m².

APPLICATION

SEMIN AIRLESS 3 IN 1 can be sprayed with all kinds of Airless machines adapted to spraying coatings. Recommended nozzle: 627.

For optimum results, we recommend following this method:

- Spray a first layer of the coating about 300 to 400 g/m², to show up the defects on the surface. Spray at a distance of about 80 cm from the relevant surface.
- Check over the surface carefully.
- Spray the final layer of about 1.2 kg/m².

This coating does not need smoothing.

STATE OF THE ART AIRLESS COATING

State of the art airless coating, ready to use, bright white and with great coverage and a deep, dry, matt finish.

ADVANTAGES

- 3 in 1.
- White and covering capacity.
- Even appearance without smoothing.
- Stays matt in low-angled light.
- Does not run.
- Does not crack.
- No spray spectra or mists in corners.

APPLICATION TIP

Do not dilute.

AFNOR classification: NFT 36.005.
Family III - Class 2

