



SEM-PRO

READY TO USE WALLPAPER PASTE FOR LIGHT OR HEAVY WALLPAPER

TECHNICAL DEFINITION

SEM-PRO is a ready-to-use paste for hanging standard light or heavy wallpapers. It offers excellent sliding properties. Transparent when dry. Does not stain.

COMPOSITION AND APPEARANCE

Starch based paste containing water and preserving agents.

SEM-PRO is a smooth translucent gel.

ACCEPTED SUBSTRATES

- Plasterboard.
- Plaster blocks.
- Concrete or cement render.

COVERING

Light or heavy wallpaper.

DOCUMENTS TO CONSULT

DTU 59.4.

TECHNICAL CHARACTERISTICS

Density: Approximately 1.

PACKING

15 kg pails.

STORAGE

6 months in unopened original packing protected from cold and extreme heat (storage temperature range between 0 and 30°C) 1 to 2 months after opening.

APPLICATION

PRECAUTIONS FOR USE

The temperature during application and drying should be between 8 and 35° C.

PREPARATION OF SURFACES

Substrates must be sound, dry and free of dust, normally absorbent and must be in conformity with DTU 59.4. On absorbent surfaces, (plaster blocks, plasterboard), first apply our PRIM-PLAQUE primer. Remove old wallpaper.

Sand, wash and rinse old paint. Strip any flaking paint.

On soft surfaces, apply our DURCIFOND hardener.

To help slide drops to match it may be advisable to size the substrate with diluted SEM-PRO using 1 part paste to 3 or 4 parts water.

PASTING THE COVERINGS

Apply paste to the back of the covering, spreading it evenly and in sufficient amounts.

Allow to soak into the covering, referring to the instructions of the maker (approximately 5 to 10 min). It is possible to paste up several lengths in advance, not allowing the paste to dry more than 40 minutes.

Fold back the ends of each length, bringing them end-to-end.

HANGING THE WALL-COVERINGS

Hang the length from the top of the wall and smooth out from top to bottom and center to sides. Use a sponge to mop up any excess adhesive and finish off the joins with a roller.

Clean up fresh paste stains using a damp sponge.

CONSUMPTION 200 g/m².

GENERAL PURPOSE WALLPAPER PASTE

SEM-PRO is ready-to-use, recommended for the fast and easy hanging of basic wall papers without any risk of marks or lumps.

ADVANTAGES

- Very high efficiency
- Excellent sliding properties.
- Transparent when dry.

APPLICATION TIP

Close the pail to seal it after use and store in a cool and dry place.

