



CE 78 LIGHT

JOINTING FILLER FOR PLASTERBOARD

TECHNICAL DEFINITION

Jointing filler in powder form designed specially for jointing tapered edge plasterboard in combination with jointing tape. Working time once mixed: 2 hours.

COMPOSITION AND APPEARANCE

Plaster, calcium carbonate, lightening filler, resin and various additives. The resulting paste is white.

ACCEPTED SUBSTRATES

All types of plasterboard with or without insulation (glass wool, rock wool, polystyrene) with tapered edges and paper facing.

COVERING

- Primer undercoat for plasterboard.
- Plaster-based smoothing filler.
- Microprofil.

DOCUMENTS TO CONSULT

- DTU 25.41 and 25.42.
- Standard NF EN 13963.
- CE marking.
- DoP.

TECHNICAL CHARACTERISTICS

- No crack formation up to 5 mm thickness.
- Powder density: 0.65.
- Paste density: 1.15 (1.6 for traditional filler).
- Setting time: 2 to 4 hours.

PACKING

15 kg bags.

STORAGE

9 months in unopened original packing protected from damp.

APPLICATION

PRECAUTIONS FOR USE

The temperature during application and drying must be between 5 and 30°C.

Do not apply onto a damp surface.

Do not use on a frozen substrate.

Do not use mix that has begun to set.

PREPARATION OF SURFACES

Cut edges of boards must be bevelled and dusted.

MIXING FACTOR

9.5 to 10 litres of water per 15 kg sack.

APPLICATION

Before jointing, fill gaps between boards and any irregular joints, and repair any damaged board.

Apply manually by using a 10 or 15 cm filling knife and apply the tape-milled face against the board. Then apply a finish coat. Allow to dry and finish to cover the tape.

Also cover screw heads.

Apply a tape into the ceiling joints and ensure that the concrete is free of any sign of mould-release oil.

For vertical protruding angles, use reinforced tape (metal side against the board) or a metal angle bead.

Application on Microprofil

ASSOCIATED TAPE

All types of paper tape.

CONSUMPTION

Around 210 g/m² of board (350 g/m² for traditional filler).

DRYING TIME

Recoating is possible 4 to 5 hours after application of the first coat.

JOINTING FILLER FOR PLASTERBOARD

The "light" formulation reduces the weight of the sack, while at the same time producing the same yield as traditional filler.

ADVANTAGES


- Same yield as a 25 kg sack.
- Quick setting.

APPLICATION TIP

To save time on the building site, remember to cut strips of jointing tape to length beforehand.

WARNING

Excessive mixing or mixing that is too fast can change the lightweight properties of the product and increase consumption.



NET WEIGHT **15 kg**
Same yield as **25 kg**

