



SEMSATIN

INTERIEUR

Satin acrylic paint. For interior use.

SUITABLE SUBSTRATES

All primed interior substrates, walls and ceilings: plaster, wood, old paintwork and sealants.

INSTRUCTIONS FOR USE

PREPARATION OF SUBSTRATES

Substrates must be prepared according to the rules of DTU 59.1. New plasterboards should be primed with SEMPRIM primer.

APPLICATION

When the primer is completely dry, apply two coats SEMSATIN.

TOOLS

Brush, roller and airless spray gun (517 nozzle).

TOOLS CLEANING

With water.

YIELD

10 to 12 m² per litre and per coat.

DRY (AT 23°C – 50% RH)

Drying time : 2 hours.

Dry-to-recoat time : 12 hours

PRECAUTIONS FOR USE

- Do not apply at a temperature lower than +5°C relative humidity higher than 70%.
- Do not apply to overheated substrates.
- Do not apply to damp substrates.

TECHNICAL INFORMATION

PACKAGING

Plastic buckets of 4 and 15 liters.

STORAGE

18 months in unopened packaging. Store away from frost.

SPECULAR GLOSS

33% from an angle of 85°.

WET ABRASION RESISTANCE

Standard NF EN 13300: class 2.

DRY EXTRACT (BY WEIGHT)

56%

DENSITY

1.4 (standard EUR PL 004).

ADVANTAGES

- High Covering Power
- Washable

Regulations in force :

Standard AFNOR T 36005
FAMILY I – CLASS 7b2.

Safety :

Aqueous phase product,
not subject to labelling.

Emissions in indoor air (according to ISO 16000) :

This product contains less
than 1g/l of VOCs.

