

## SEM<sup>M</sup>MAT

INTERIOR



**Indoor matt acrylic paint.  
Odourless.**

### SUITABLE SUBSTRATES

All interior substrates, walls and ceilings: plasterboard, concrete, old paintwork and coated substrates in good condition.

### INSTRUCTIONS FOR USE

#### PREPARATION OF SUBSTRATES

Substrates must be prepared according to the rules of DTU 59.1.

#### TOOLS

Brush, roller and airless spray gun (519 nozzle).

#### TOOLS CLEANING

With water.

#### YIELD

8 to 9 m<sup>2</sup> per liter.

#### DRYING (AT 23°C – 50% RH)

Dry time: 2 hours.

Dry-to-recoat time: 6 hours

#### PRECAUTIONS FOR USE

- Do not apply at a temperature lower than +8°C relative humidity higher than 70%
- Do not apply to overheated substrates.
- Do not apply to damp substrates.

#### TECHNICAL INFORMATION

##### PACKAGING

Plastic buckets of 4 and 15 liters.

##### STORAGE

18 months in unopened packaging. Store away from frost.

##### SPECULAR GLOSS

< 3 % from an angle of 85°.

##### WET ABRASION RESISTANCE

Standard NF EN 13300: class 2  
(loss of film thickness > 5 µ < 20 µ, after 200 cycles).

##### DRY EXTRACT (BY WEIGHT)

57 %

##### DENSITY

1.5 (standard EUR PL 004).

### ADVANTAGES

- High yield
- High covering power

### Regulations in force :

Standard AFNOR T 36005  
FAMILY I – CLASS 7b2.

### Safety :

Aqueous phase product,  
not subject to labelling.

### Emissions in indoor air (according to ISO 16000) :

This product contains less  
than 1g/l of VOCs.

