



COLLE FRISES

SPECIAL ADHESIVE FOR DECORATIVE FRIEZES

PERFECT FOR WALLPAPER SEAMS

TECHNICAL DEFINITION.

A white glue, transparent after drying, for gluing decorative friezes onto wallpaper or vinyl wallpaper. Can also be used to glue stickers and allows you to re-stick wallpaper seams when the wallpaper has come away.

COMPOSITION AND APPEARANCE

Glue containing starch, water, emulsion resin. The paste is white and transparent after drying.

SUITABLE SUBSTRATES.

Interior walls. For gluing paper or vinyl friezes onto wallpaper or vinyl wallpaper.

REFERENCE DOCUMENTS.

DTU 59.4: Application of wallpaper and wall coverings

TECHNICAL FEATURES

- Drying time: 24 to 48 hours.
- Paste density: <1.1 kg/L.

PRECAUTIONS FOR USE.

The temperature on application and during drying must be between +10 and 35°C.

Do not apply at a humidity levels above 65 %.

Read the frieze, wallpaper or sticker manufacturer's instructions carefully.

SAFETY.

Safety data sheet available on www.quickfds.com. Please read it before use.

Keep out of reach of children.

In the event of swallowing, immediately consult a doctor and show him the packaging or label.

Wearing gloves is recommended.

EUH 208 Contains 1,2-benzisothiazol-3(2H)-one and a mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC No. 247-500-7]; 2-methyl-2H-isothiazol-3-one [EC No. 220-239-6] (3:1)(55965-84-9). May trigger an allergic reaction.

PREPARATION OF SUBSTRATES.

They must comply with DTU, i.e. be clean, dry, hard, cohesive, sound, dust-free and free of any trace of formwork oil.

CONSUMPTION.

250 g for approximately 15 m of frieze.

APPLICATION TYPE.

Wash down and degrease old coverings. On freshly hung wallpapers, allow to dry for 24 hours before affixing the decorative frieze.

Moisten the frieze with a wet sponge and let it soak for about ten minutes.

Use the applicator to apply the frieze glue to the reverse side of the frieze. Apply uniformly and evenly over the entire surface.

Affix the frieze onto the substrate and work in meticulously. Remove any excess glue before drying with a damp sponge.

DRYING TIME.

Depends on substrate, weather conditions and application thickness.

As a general rule, the product will dry in 24-48 hours.

STORAGE.

12 months in original, unopened packaging away from frost and high temperatures.

GLUE FOR DECORATIVE FRIEZE, WALLPAPER SEAMS AND STICKERS

The glue's strengthened adhesion bonds it effectively to all types of wall coverings, even impermeable ones, without leaving stains.

ADVANTAGES

- Tube with applicator
- Ready mix
- Does not stain
- Touch up wallpaper strips
- Greater adhesion

