



1 PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

Once fixed on the roof timbers, clip the furring to install a plasterboard ceiling.

Trade name	Product name	560-45 long hangers
Product dimensions	Height (in mm)	4
	Width (in mm)	44
	Length (in mm)	560
	Weight (in kg)	0.182
Material	Galvanised steel	
Consumption	Average consumption (per m ²)	1.8
	Average consumption (per m)	0.6
Install information : all products	Unit pack : type	pack
	Unit pack : height (in cm)	5
	Unit pack : width (in cm)	6.5
	Unit pack : weight (in kg)	5
	Unit pack : depth (in cm)	56
	Number of products / parcels (in items)	50

1 ADVANTAGES

- Classic and fast install
- Suitable for all types of 45 furrings on the market (certification)

1 REFERENCES TO TECHNICAL DOCUMENTS

- Customs nomenclature : 73089059
- Regulations : MRF Test Report 14 26044520
Compliant with DTU 25.41

1 REFERENCES & PACKAGINGS

- Product reference : A 03450
- Barcode : 3585501034503
- Packaging : Pack of 50 items.

1 AREA OF APPLICATION

This hanger is used for installing all suspended ceilings and false ceilings.

1 INSTRUCTIONS FOR USE

1. Fixing of hangers on the edge of the roof timbers, perpendicular to the rafter.
2. Insert the furring and turn until hearing the "click"



1.

2.

DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?

- Screws : The screws are attached to the hangers on the rafters.
- Furrings Insert in the hangers until hearing the "click".