



PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

Securing a threaded rod for a false ceiling.

Trade name	Product name	Female threaded head screw
Product dimensions	Height (in mm)	10
	Width (in mm)	10
	Length (in mm)	55
	Weight (in kg)	0.013
Material	Galvanised steel	
Consumption	Average consumption (per m ²)	1.8
	Average consumption (per m)	0.6
Install information : all products	Unit pack : type	Box
	Unit pack : height (in cm)	7.8
	Unit pack : width (in cm)	10.8
	Unit pack : weight (in kg)	1.3
	Unit pack : depth (in cm)	16.8
	Number of products / parcels (in items)	100

ADVANTAGES

- Classic and fast install
- Strength of the screw

REFERENCES TO TECHNICAL DOCUMENTS

- Customs nomenclature : 73181541

REFERENCES & PACKAGINGS

- Product reference : A02978
- Barcode: 3585501029783
- Packaging : Box of 100 items.
864 boxes per pallet.

AREA OF APPLICATION

The female threaded head screw is used for ceiling renovation.

INSTRUCTIONS FOR USE

1. After having drilled a hole in the wood, screw in the female threaded head screw, then insert the threaded rod in the female threaded head screw and the pivot rod bracket on the threaded rod.
2. Then fix the furring to the pivot rod bracket.



1.



2.

DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?

- Threaded rod: to insert on the female threaded head screw
- Pivot rod bracket: to insert on the threaded rod