



# PROLISS

## READY-TO-USE ULTRA-LIGHT AIRLESS COATING

- + EASY TO SMOOTH AND SAND
- + IDEAL FOR MANUAL ROLLER OR MACHINE APPLICATION
- + HIGH PERFORMANCE DURING USE
- + PLASTER WON'T CLOG HOSES UNDER HIGH PRESSURE

### USES.

Ready-to-use ultra-light interior plaster that can be applied using machines. Grey, fine-grained and very efficient per litre of product.

### SURFACES.

For interior use, for dry substrates of cement, lime, plaster or concrete as well as painted surfaces.

### MACHINES.

Graco Marks V & VII, Graco T-Max 506, Wagner PS 3.39, etc. Nozzles: 0.039 and larger.

### CHARACTERISTICS.

- Consumption: approx. 0.8-2 m<sup>2</sup>/l.
- Second coat can be applied after 24 hours.
- Coat thickness: 1-4 mm.
- Dry matter content: 65%.
- Density: 1.1.
- Do not use at temperatures below 8 °C.

### INSTRUCTIONS FOR USE.

Before using the product, mix it until it is uniform. Do not apply to damp or frozen substrates. The substrate should be clean, stable and free from grease and dust. The product may be applied to plasterboards with a roller, spatula or machine.

Before applying the plaster, smooth any uneven areas and fill in any defects (such as chipped edges, etc.).

When pointing, embed tape in the first coat.

The next coat can be applied after 6 hours.

An open package can be used the following day.

### STORAGE.

Shelf life: 18 months from the date of manufacture.

Store in the original, intact packaging; protect against frost, sunlight and high temperatures.

### PACKAGING.

15-l bags.



USAGE



MANUAL APPLICATION



MANUAL APPLICATION



MECHANICAL APPLICATION

# SEMIN

1a, rue de la Gare - F-57920 KEDANGE-SUR-CANNER

Tél. +33 (0)3.82.83.53.57 - Fax : +33 (0)3.82.83.93.33

[www.semin.com](http://www.semin.com)



VOC content <1 g/L



MADE IN FRANCE

