



PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

Link between the wooden timbers and the metal frame. Articulated hanging accessory for plasterboard ceilings under wooden floors.

| Trade name | Product name | Articulated hangers |
|---|---|---------------------|
| Product dimensions | Height (in mm) | 30 |
| | Width (in mm) | 33 |
| | Length (in mm) | 69 |
| | Weight (in kg) | 0.029 |
| Material | | Galvanised steel |
| Consumption | Average consumption (per m ²) | 1.8 |
| | Average consumption (per m) | 0.6 |
| Install information : all products | Unit pack : type | pack |
| | Unit pack : height (in cm) | 12 |
| | Unit pack : width (in cm) | 18,5 |
| | Unit pack : weight (in kg) | 1,55 |
| | Unit pack : depth (in cm) | 14 |
| | Number of products / parcels (in items) | 50 |

ADVANTAGES

- Classic and fast install
- The mobile "L" rotates so that the rod is vertical

AREA OF APPLICATION

Installation of a plasterboard ceiling with furrings

REFERENCES TO TECHNICAL DOCUMENTS

- Customs nomenclature: 73089059
- Regulations : EN 13964 Compliant with DTU 25.41

REFERENCES & PACKAGINGS

- Product reference : A03079
- Barcode : 3585501030796
- Packaging : Box of 50 items.
160 boxes per pallet.

MISE EN ŒUVRE

1. Fixed on the sloping rafter by SEMIN screws of a minimum 25 mm, the threaded SEMIN rod of a 6 mm diameter in the mobile "L" is vertical and held by the nut.




1.

2. Screw the pivot rod bracket to the threaded rod



2.

3. Clip the pivot rod bracket on the furring.



3.

Caution :
The spaces between hangers must comply with DTU 25-41.

DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?

- Screws : to secure the articulated hanger with a screw
- Threaded rods: placed in the mobile "L" of the articulated hanger

- Nuts : to maintain the threaded rod in the mobile "L" of the articulated hanger
- Pivot rod bracket : to fix to the threaded rod
- Furrings : to fix to the pivot rod bracket