

1 PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

Corner guard profile made of aluzinc for plasterboards

Trade name	Product name	Semin micro profile 3m
Product dimensions	Height (in mm)	20
	Width (in mm)	32
	Thickness (in mm)	0,4
	Length (in mm)	2500
	Weight (in kg)	0.25
	Number of links/flanges over the length	20
Material		Aluzinc
Consumption	Average consumption (per m ²)	1,8
	Average consumption (per m)	0,6
Install information : all products	Unit pack : type	Carton
	Unit pack : height (in cm)	5
	Unit pack : width (in cm)	6
	Unit pack : weight (in kg)	5,86
	Unit pack : depth (in cm)	252
	Number of products / parcels (in items)	20

2 ADVANTAGES

- Quick installation
- Optimal bonding between the coating and the flanges of the profile.

3 REFERENCES TO TECHNICAL DOCUMENTS

- Customs nomenclature : 76169990
- Regulations : EN 10215 MDB label for the packaging

4 REFERENCES & PACKAGINGS

- Product reference : A04638
- Barcode : 3585501046384
- Packaging : Carton of 20 items
147 cartons per pallet.

5 AREA OF APPLICATION

- Recommended for finishing the outward facing corners formed by plasterboards.

6 INSTRUCTIONS FOR USE


The profile is mechanically secured using a "clinch-on" or staples on the plasterboards. The 1st coat is applied using powder-type "CE78" compound for plasterboards (all brands).



Finishing the corner (2nd coat) is done applying a 1mm thick powder or ready-mix finishing coat of the "CE78 light paste" type (all brands). **Always check with the manufacturer of the coating that the product is compatible with the profile used.** This profile is characterised by the speed of installation and by the optimal bonding between the coating and the flanges of the profile.

DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?

- CE 78 : For the first coat
- CE 78 light: For the second coat



1 PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

Corner guard profile made of aluzinc for plasterboards

Trade name	Product name	Semin micro profile 3m
Product dimensions	Height (in mm)	20
	Width (in mm)	32
	Thickness (in mm)	0,4
	Length (in mm)	2500
	Weight (in kg)	0.3
	Number of links/flanges over the length	20
Material		Aluzinc
Consumption	Average consumption (per m ²)	1,8
	Average consumption (per m)	0,6
Install information : all products	Unit pack : type	Carton
	Unit pack : height (in cm)	5
	Unit pack : width (in cm)	6
	Unit pack : weight (in kg)	7,1
	Unit pack : depth (in cm)	302
	Number of products / parcels (in items)	20

2 ADVANTAGES

- Quick installation
- Optimal bonding between the coating and the flanges of the profile.

3 REFERENCES TO TECHNICAL DOCUMENTS

- Customs nomenclature : 76169990
- Regulations : EN 10215 MDB label for the packaging

4 REFERENCES & PACKAGINGS

- Product reference : A04639
- Barcode : 3585501046391
- Packaging : Carton of 20 items
147 cartons per pallet.

5 AREA OF APPLICATION

- Recommended for finishing the outward facing corners formed by plasterboards.

6 INSTRUCTIONS FOR USE

The profile is mechanically secured using a "clinch-on" or staples on the plasterboards. The 1st coat is applied using powder-type "CE78" compound for plasterboards (all brands).



Finishing the corner (2nd coat) is done applying a 1mm thick powder or ready-mix finishing coat of the "CE78 light paste" type (all brands). **Always check with the manufacturer of the coating that the product is compatible with the profile used.** This profile is characterised by the speed of installation and by the optimal bonding between the coating and the flanges of the profile.

DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?

- CE 78 : For the first coat
- CE 78 light: For the second coat