

SEALED ACCESS PANEL WATER/AIR/DUST/SMOKE



ACOUSTIC
IMPROVEMENT

INVISIBLE
ACCESS PANEL

- Aluminium profile frame secured by «Tox» connections
- Double-sided EPDM seal along the whole circumference
- Safety catch on both sides
- Hidden latches
- GKB plaster panel
- Fitting instructions and template
- Can be tiled

ACOUSTIC IM-
PROVEMENT
TESTED AT
47 DB

SIZES AND REFERENCES 12,5 mm BOARD

| DIMENSIONS IN MM | INTERNAL DIMENSIONS LENGTH x WIDTH | WEIGHT IN KG | REFERENCE |
|------------------|---------------------------------------|-----------------|-----------|
| 300 x 300 | 240 x 240 | 1.9 | A04539 |
| 400 x 400 | 340 x 340 | 2.8 | A04540 |
| 500 x 500 | 440 x 440 | 4 | A04541 |
| 600 x 600 | 540 x 540 | 5.1 | A04542 |
| 600 x 800 | 540 x 740 | 6.7 | A04543 |

Non-stocked items – 3/4 weeks delivery lead time.

ACOUSTIC IM-
PROVEMENT
TESTED AT
49 DB

SIZES AND REFERENCES 12,5 mm 2 BOARDS

| DIMENSIONS IN MM | INTERNAL DIMENSIONS LENGTH x WIDTH | WEIGHT IN KG | REFERENCE |
|------------------|---------------------------------------|-----------------|-----------|
| 300 x 300 | 240 x 240 | 2.7 | A04544 |
| 400 x 400 | 340 x 340 | 5.7 | A04545 |
| 500 x 500 | 440 x 440 | 6.6 | A04546 |
| 600 x 600 | 540 x 540 | 8.4 | A04547 |
| 600 x 800 | 540 x 740 | 11.3 | A04548 |

Non-stocked items – 3/4 weeks delivery lead time.

PARTICULARITIES OF APPLICATION

- Fit to wall or ceiling (do not walk on it).
- Water permeability tested according to EN 1027 standards: 2000-06 and EN 12208: 1999-11; Report No. 104 32588.
- Smoke tightness tested according to DIN EN 1634-3 standards: 2005-3.
- Air permeability tested according to EN 1026 standards: 2000-09 and EN 12207: 1999-11; Report No. 104 31394/1 and 104 31394/4.
- Water-tightness report: No. 14-002774-PR01.
- Suitable for wet rooms.

QUALITY ASSURANCE

Production quality control is integrated into the manufacturing process of each item. The raw materials and external components undergo the quality control system on arrival of the goods.

MATERIALS

| | |
|--|--|
| Parts of the frame | Bar profiles, quality Eloxale ALMgSi 0.5 F22 |
| Stopping angle, Stopping device, Angle section, Mounting sheet | Sheet steel, galvanised DC 01 Am 1.5 mm |
| Spacer sheet, drill template | Sheet steel, galvanised DX51D/Z275 1.00 mm |
| Plaster board | Board |
| Latch | Steel/plastic |
| Seal | EPDM lip seal |
| Quick mounting screws | Steel |

