



# SEM-DECOLLEUR

## WALLPAPER STRIPPER

### TECHNICAL DEFINITION

SEM-DECOLLEUR is a concentrated substance, which is used diluted and makes the stripping of old wallpaper easier.

### COMPOSITION AND APPEARANCE

Combination of surface-active agents. Fluorescent yellow, translucent liquid.

### SUITABLE SUBSTRATES

Standard, heavy or special wallpaper, vinyl wallpaper, expanded vinyl wallpaper, etc.

### TECHNICAL CHARACTERISTICS

- Density: 1.06
- pH: 12 (approximately).
- More than 90 % biodegradable.

### PACKING

5 litre cans and 1 litre bottles.

### STORAGE

12 months in unopened original packing protected from frost and high heat (storage temperature range between 5 and 35° C).

### APPLICATION

#### PRECAUTIONS FOR USE

Avoid prolonged contact with the skin and splashes in the eyes. Do not swallow. Keep out of children's reach.

Product labelled as hazardous. Contains sodium metasilicate. Refer to the safety label on the packaging. Observe the precautions for use and the safety advice. Safety data sheet available at [www.quickfds.com](http://www.quickfds.com), read before use.

#### APPLICATION

The product needs to be diluted in warm or cold water:

- Standard wallpaper: 100 ml of concentrated product in 10 litres of water.
- Heavy or special wallpaper: 200 ml of concentrated product in 10 litres of water.

Apply the appropriate dilution on the wallpaper, using a sponge. Allow to soak for 10 to 15 minutes. Strip the wallpaper widths one after the other using a spatula.

If using on vinyl wallpaper, streak the covering with a metal brush to allow the paper to soak.

#### CONSUMPTION

100 ml for approximately 30 m<sup>2</sup> of treated area.

## HIGH-YIELD WALLPAPER STRIPPER

Thanks to its highly concentrated formulation, SEM-DECOLLEUR makes the stripping of old wallpaper quicker and more effective.

### ADVANTAGES

- SEM-DECOLLEUR allows to strip old wallpaper in no time, without damaging the original substrate.
- Very high yield, 1 l of wallpaper remover for approximately 300m<sup>2</sup>.

### APPLICATION TIP

For strippable wallpaper, the top layer must be stripped beforehand.

Allow the product to soak for about 10 minutes before stripping the wallpaper with a spatula.

Protect the floor beforehand.

