



# CUISINE & SALLE DE BAIN

## LIGHT FINISHING PLASTER

### TECHNICAL DESCRIPTION

Ready-to-use light waterproof paste plaster for finishing walls in damp rooms: kitchen and bathrooms.

Prepare thoroughly before painting of hanging wallpaper.

### COMPOSITION AND APPEARANCE

Resin emulsion, calcium carbonate, light filler, waterproof additive and various adjuvants.

The resulting paste is green in colour.

### SUITABLE SURFACES

- Plasterboard.
- Plaster tiles.
- Earthenware tiles.
- Concrete.
- Cement rendering.
- Kitchen and bathroom repair and filling plaster.

### COATINGS

- Paint.
- Wallpaper.

### APPLICATION

#### PRECAUTIONS FOR USE

The temperature for application and during drying must be between 8 and 35° C.

Do not use on wet surfaces.

#### PREPARATION OF SURFACES

They must meet DTU 59.1, i.e. clean, dry, free from dust and all traces of moulding oil.

#### APPLICATION

It is applied using a painter's knife or a plasterer's trowel.

#### THICKNESS OF APPLICATION

Up to 1 mm in one pass.

#### COVERAGE

About 150 to 200 g/m<sup>2</sup>.

#### DRYING TIME

Depends on ambient conditions, nature of the surface and thickness of application.

On average, the plaster is dry in 12 to 24 hours.

#### TECHNICAL SPECIFICATIONS

- Grain size: Up to 0.2 mm.
- Adhesion: complies with NFT 30 608.
- pH: 8
- Dry weight: 65%.

#### PACKING

1 and 5 kg pails.

#### STORAGE

6 months in the original undamaged packaging protected from frost and heat sources

## LIGHT KITCHEN AND BATHROOM FINISHING PLASTER

Special finishing plaster for damp rooms (kitchen and bathroom), before painting or wallpapering.

### ADVANTAGES

- Good moisture resistance.
- Easy and quick to use.
- Free from solvent, clean tools in water.

### APPLICATION TIP

Do not add water so as not to damage the qualities of the product.

AFNOR Classification NFT 36.005  
Family III - Class 2.

