



PAVEMENT PRO

MULTI-BINDER JOINT FILLER FOR PAVEMENT

PAVEMENT PRO is composed of several high-performance synthetic binders, of a hydraulic binder and of high-quality minerals. Specially designed for pavement jointing, this innovative product with outstanding mechanical characteristics has the advantage of being very easy to implement.

APPLICATION FIELD.

Pavement jointing for outdoor laying-out in private properties—lanes, garage entrances, terraces, etc.—and urban spaces—pavements, squares, pedestrian areas, car parks, etc.

The multi-binder joint filler stabilizes the cobblestones together and allows for a long-lasting effect by ensuring the flatness of the pavement, in particular on driveways.

It also has a considerable weed-control effect. The broad range of colours available allows to match the colour of most cobblestones on the market.

PACKING.

48 bags of 25 kg each on lost pallet.

Protection: plastic-wrapped.

APPLICATION

APPLICATION.

Lay out a 2-3 cm thick seating with 0/2 - 0/4 mm sand or crushed stone.

Lay the cobblestones on the seating, making sure to complying with the maximum and minimum specified joint thickness.

Spread out PAVEMENT PRO and fill the joints evenly with a long-handled scrubbing brush.

Compact the surface with a rubber-protected rammer.

Add more PAVEMENT PRO until the joints are saturated.

Make sure that the cobble surface is perfectly clean to prevent PAVEMENT PRO from leaving traces when wet (these traces disappear with time).

Drizzle water over the whole jointed area.

Drizzle again 2 or 3 times at 10-15 min interval to make sure that PAVEMENT PRO is wet down to the bottom of the cobblestones.

PAVEMENT PRO will set within 24-48 hrs depending on the weather conditions.

PRECAUTIONS FOR USE

The pavement must be made according to professional standards and the surface must be dry.

PAVEMENT PRO can only be used on top of a calibrated draining seating – 0/6 sand, 0/2 - 0/4 mm crushed or vitrified stone.

Joint thickness must range between 3 and 10 mm.

Do not use when temperatures are below 5°C or in the rain.

Liability of the manufacturer is limited to product replacement.

For subsequent maintenance, avoid using a pressure washer.

CONSUMPTION.

25 kg of PAVEMENT PRO can treat a surface area of 5-8 m² depending on joint thickness and cobblestone format.

PAVEMENT PRO has a density of 1.9 g/cm³. This varies according to the intensity of the compacting process.

PRECAUTIONS FOR USE.

Keep out of children's reach.

Product labelled as hazardous. Contains cement: gloves should be worn. Refer to the safety label on the packaging. Observe the precautions for use and the safety advice. Safety data sheet available at www.quickfds.com, read before use.

MULTI-BINDER JOINT FILLER FOR PAVEMENT

PAVEMENT PRO is composed of several high-performance synthetic binders, of a hydraulic binder and of high-quality minerals.

Specially designed for pavement jointing, this innovative product with outstanding mechanical characteristics has the advantage of being very easy to implement.

ADVANTAGES

- Stabilizes the cobblestones together and adapts to ground movements.
- Leaves the pavement permeable.
- High resistance to weather changes.
- Provides a weed-control effect.

APPLICATION TIP

Make sure that PAVEMENT PRO goes all the way down to the bottom of the cobblestones by compacting the surface carefully, renewing the process 2 or 3 times.

