



SEM-MURALE

ADHESIVE FOR FIBREGLASS AND TEXTILE WALL COVERINGS

TECHNICAL DEFINITION

SEM-MURALE is an odorless water based paste in ready-to-use form for flexible wall coverings.

Suitable for indoor use on walls and ceilings.

May be used for hanging fibre glass even in wet rooms.

COMPOSITION AND APPEARANCE

Emulsion resin containing starch, rheological agent and various additives. The paste is white.

ACCEPTED SUBSTRATES

INTERIOR WALLS AND CEILINGS

- Concrete.
- Cement render.
- Plaster board.
- Plaster blocks.
- Primer undercoat.

COVERING

Textiles with or without paper backing. Wide fabric rolls on foam or felt. PVC coverings with paper or polyester backing. Glass fabrics for painting. Thin expanded polystyrene. Depron.

TECHNICAL CHARACTERISTICS

- Working time: 5 to 10 minutes.
- Open pot life: 30 minutes.
- Setting time: 12 to 24 hours.
- Density: approximately 1.
- Dry matter: 14 %.

ASSOCIATED PRODUCTS

DURCIFOND for crumbling and powdery surfaces. PRIM-PLAQUE as undercoat primer for plaster-board.

PACKING

1 - 5 - 10 and 20 kg pails.

STORAGE

6 months in unopened original packing protected from cold and extreme heat

ADHESIVE FOR FIBREGLASS AND TEXTILE WALL COVERINGS


SEM-MURALE is a ready to use resin-based paste suitable for the application of all flexible wall coverings and for glass fibre even in wet rooms.

ADVANTAGES

- Solvent- and odour-free.
- Fungicidal.
- Low consumption.

APPLICATION TIP

Always store the covering for 48 hours in advance in the room where it is to be hung.



APPLICATION

PRECAUTIONS FOR USE

Close the pail after use. Working temperature: 8 to 55° C. On sealed surfaces, use SEM-SOL XXL.

PREPARATION OF SUBSTRATES BEFORE APPLICATION

Substrates must be clean, sound, dry, solid, smooth, flat and normally absorbent. Strip old wallpaper or color washes. Fill as necessary using suitable filler.

On soft, crumbling, powdery or very absorbent surfaces, apply our DURCIFOND hardener.

Sand, scrape and dust old painted surfaces.

APPLICATION AND PASTING

Follow the recommendations of the manufacturer.

Apply by pasting the substrate with a roller, brush or serrated spatula. Paste only an area corresponding to 2 drops at most. Hang the drop and smooth from the centre to the outside.

Clean off any excess adhesive using a sponge.

Clean tools in water.

CONSUMPTION

From 150 to 250 g/m² depending on covering and application tool.

