



CE 3000 SEMIN RENOVATION

ALL-ROUND RENOVATION RENDER INTERIOR

TECHNICAL DEFINITION

CE 3000 is a multifunction powder filler for interior use.

GLUES: Plaster blocks. Plaster boards. Jointing tapes.

STICKS: Decorative polystyrene elements.
Polystyrene roses and mouldings

FILLS: Holes and cracks.

FLATTENS: Walls and ceilings.

SMOOTHS: All substrates.

DECORATES: Decoration with a roller.

COMPOSITION AND APPEARANCE

Powdered render composed of plaster, calcium carbonate, resin, cellulose fibre and various additives. The obtained paste is white.

SUITABLE SUBSTRATES

All type of interior substrates.

COVERING

Once the render is completely dry, it can be covered with any type of paint, plaster-based render, paste-like render, wallpaper paste or wall covering.

DOCUMENTATION FOR REFERENCE

- DTU 59.1: painting work.

TECHNICAL SPECIFICATIONS

- Grain size: fine.
- Setting time: 2 hours.

PACKING

5 - 15 - 25 kg bags. 15 kg pails.

STORAGE

9 months in non-opened original packing, sheltered from dampness.

APPLICATION

PRECAUTIONS FOR USE

Temperature throughout the application and drying process must range between 5 and 30° C. Do not use the paste once it has began to set.

PREPARATION OF THE SUBSTRATE

The substrate must comply with regulation DTU 59.1, i.e. be clean, dry, free of dust and of any trace of formwork dismantling oil. Wash old drop-finish render. Rub down old paintwork.

MIXING PROPORTION

10 to 12 l of water per 25 kg sack. Mixing is preferably mechanical.

APPLICATION

Using a smoothing trowel, plaster knife or spatula for smoothing work. For a decorative aspect, use a roller, brush or sponge.

CONSUMPTION

From 0.4 kg/m² (smoothing) to 2.5 kg/m² (decoration).

DRYING TIME

Drying time depend on the nature of the work.

ALL-ROUND RENOVATION RENDER

CE 3000 is a multifunction powder filler for interior use: plaster blocks, plaster boards, jointing tapes...

ADVANTAGES

- Dries quickly.
- All-round, multi-purpose product.
- Ideal product to render old painted fibreglass cloth.

APPLICATION TIP

Simply adapt mixing rate of CE 3000 according to the nature of the work.

AFNOR classification: NFT 36.005.
Family III – Class 3.

