



1 PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

Designed for the installation of a suspended or sloping ceiling on an uneven substrate.

Trade name	Product name	Quick adjustable hanger
Product dimensions	Height (in mm)	140 (with spring)
	Width (in mm)	440
		(pivot compatible with 45 and 47 furrings)
	Thickness (in mm)	11
	Thickness of the steel	0.8/10th
	Weight (in g)	35
	Spring for smooth rod (in mm)	4
Material		Galvanised steel
Consumption	Average consumption (per m ²)	1,8
	Average consumption (per m)	0,6
Install information : all products	Unit pack : type	box
	Unit pack : height (in cm)	11,5
	Unit pack : width (in cm)	155
	Unit pack : weight (in kg)	1,9
	Unit pack : depth (in cm)	30
	Number of products / parcels (in items)	50

1 ADVANTAGES

- Fast install on uneven substrate

1 AREA OF APPLICATION

- Installation of a suspended or sloping ceiling on an uneven substrate.

1 REFERENCES TO TECHNICAL DOCUMENTS

- Customs nomenclature : 73089059
- Regulations : EN 13964

1 INSTRUCTIONS FOR USE

Squeeze the two tabs, introduce the eye rod.

1 REFERENCES & PACKAGINGS

- Product reference : AO 765
- Barcode : 358550107657
- Box of 50 items.
96 boxes per pallet.

DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?

- Eye rod: to insert into the two spring tabs) of the quick adjustable hanger (available rod sizes 125-250-500-1000mm)
- Furrings : to clip it onto the quick adjustable hanger