



**] PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS**

The securing clip is used to secure the threaded rod. It is used to attach to a thickness of metal from 4 to 10 mm.

<b>Trade name</b>	Product name	Securing clip
<b>Product dimensions</b>	Height (in mm)	60
	Width (in mm)	40
	Length (in mm)	46
	Weight (in kg)	0.028
<b>Material</b>	Black spring steel	
<b>Consumption</b>	Average consumption (per m <sup>2</sup> )	1.8
	Average consumption (per m)	0.6
<b>Install information : all products</b>	Unit pack : type	box
	Unit pack : height (in cm)	17,7
	Unit pack : width (in cm)	18
	Unit pack : weight (in kg)	18
	Unit pack : depth (in cm)	2,8
	Number of products / parcels (in items)	100

**] ADVANTAGES**

- Classic and fast install
- Strength of the clip
- Easy clipping

**] AREA OF APPLICATION**

Secured to metal beams (INP), the threaded rod is screwed into the securing clip.

**] REFERENCES TO TECHNICAL DOCUMENTS**

- Customs nomenclature : 73181541

**] REFERENCES & PACKAGINGS**

- Product reference: A02977
- Barcode : 358550102977
- Packaging: Box of 100 items.  
120 boxes per pallet.

**] INSTRUCTIONS FOR USE**

1. Attach the securing clip to the metal support
2. Then screw in the threaded rod

**DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?**

- Threaded rod: insert into the securing clip