



## PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

The bugle head screw (self-tapping bugle head nail tip screw) is used for securing plasterboard to the framework.

<b>Trade Name</b>	Product name	Screws 3.5 x35mm
<b>Product dimensions</b>	Height (in mm)	3.5
	Width (in mm)	8
	Length (in mm)	35
	Weight (in kg)	0.001
<b>Material</b>		Phosphatised steel
<b>Consumption</b>	Average consumption (per m2)	14
	Average consumption (per ml)	4
<b>Install information:</b>		
<b>All products</b>	Unit pack : type	pack
	Unit pack : height (in cm)	7,7
	Unit pack: width (in cm)	11,4
	Unit pack : depth (in cm)	14
	Unit pack : weight (in kg)	1.74
	Number of products/parcels (in items)	1000

## ADVANTAGES

- Resistant to saline fog 48 hours
- Double phosphating

## AREA OF APPLICATION

Installation of plasterboards

## REFERENCES TO TECHNICAL DOCUMENTS

- Customs nomenclature: 73181590
- Regulations: NF EN 14566 TW.CE. 0283 - 03/11  
According to European Directive 89/106/EEC (CPD)  
Compliant with DTU 25.41

## INSTRUCTIONS FOR USE

Simply screw the plasterboard onto the framework.



## REFERENCES & PACKAGINGS

- Product reference : A00204
- Barcode : 3585501002045
- Packaging : Box of 1000 items.  
10 boxes per carton, 24 cartons per pallet.

## DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?

- Profiles : The screw is used to secure the plasterboard onto the Semin metal framework
- Accessories : The screw can also be used to secure certain Semin accessories