



PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

The bugle head screw (self-tapping bugle head nail tip screw) is used for securing plasterboard to the framework.

Trade Name	Product name	Screws 4.2x70mm
Product dimensions	Height (in mm)	4.2
	Width (in mm)	8
	Length (in mm)	70
	Weight (in kg)	0.005
Material		Phosphatised steel
Consumption	Average consumption (per m ²)	14
	Average consumption (per ml)	4
Install information:		
All products	Unit pack : type	box
	Unit pack : height (in cm)	9
	Unit pack: width (in cm)	13
	Unit pack : depth (in cm)	18
	Unit pack : weight (in kg)	2,3
	Number of products/parcels (in items)	500

ADVANTAGES

- Resistant to saline fog 48 hours
- Double phosphating

AREA OF APPLICATION

Installation of plasterboards

REFERENCES TO TECHNICAL DOCUMENTS

- Customs nomenclature: 73181590
- Regulations: NF EN 14566 TW.CE. 0283 - 03/11
According to European Directive 89/106/EEC (CPD)
Compliant with DTU 25.41

INSTRUCTIONS FOR USE

Simply screw the plasterboard onto the framework.



REFERENCES & PACKAGINGS

- Product reference: A00207
- Barcode : 3585501002076
- Packaging : Box of 500 items.
4 boxes per carton, 24 cartons per pallet.

DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?

- Profiles : The screw is used to secure the plasterboard onto the Semin metal framework
- Accessories : The screw can also be used to secure certain Semin accessories