

PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

Secures the threaded rod and links the furring to the threaded rod. Strong resistance.

Trade name	Product name	Pivot rod bracket
Product dimensions	Height (in mm)	22
	Width (in mm)	25
	Length (in mm)	60
	Weight (in kg)	0.024
Material		Galvanised steel
Consumption	Average consumption (per m ²)	1.8
	Average consumption (per m)	0.6
Install information : all products	Unit pack : type	box
	Unit pack : height (in cm)	9,5
	Unit pack : width (in cm)	28
	Unit pack : weight (in kg)	18,5
	Unit pack : depth (in cm)	2,4
	Number of products / parcels (in items)	100

ADVANTAGES

- Strong resistance
- Classic and fast install
- Suitable for all 45 and 47 furrings on the market (certification)

AREA OF APPLICATION


Installation of a plasterboard ceiling with furrings.

REFERENCES TO TECHNICAL DOCUMENTS

- Customs nomenclature : 73089059
- Regulations : EN 13964 Compliant with DTU 25.41

INSTRUCTIONS FOR USE

Screw the pivot rod bracket to the threaded rod hold it in place by a nut and insert the pivot rod bracket into the furring.



REFERENCES & PACKAGINGS

- Product reference: A02711
- Barcode : 3585501027116
- Packaging : Box of 100 items.
96 boxes per pallet.

DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?

- Screws : secures the pivot rod bracket to the threaded rod
- Articulated hangers: the articulated hanger is also used to secure a pivot rod bracket