



PRODUCT DESCRIPTION & TECHNICAL SPECIFICATIONS

Once fixed on the roof timbers, clip the furring to install a plasterboard ceiling.

Trade name	Product name	Long Hollow Slab Hangers
Product dimensions	Height (in mm)	10
	Width (in mm)	70
	Length (in mm)	72
	Weight (in kg)	0.015
Material	Black spring steel	
Consumption	Average consumption (per m ²)	1.8
	Average consumption (per m)	0.6
Install information : all products	Unit pack : type	box
	Unit pack : height (in cm)	16
	Unit pack : width (in cm)	22,8
	Unit pack : weight (in kg)	15
	Unit pack : depth (in cm)	1,5
	Number of products / parcels (in items)	100

ADVANTAGES

- Classic and fast install
- Supplied with an installation accessory for security and ease of installation

AREA OF APPLICATION

Installed in the concrete or solid brick.

REFERENCES TO TECHNICAL DOCUMENTS

- Customs nomenclature : 73089059
- Regulations : EN 13964
- Compliant with DTU 25.41


REFERENCES & PACKAGINGS

- Product reference : A02982
- Barcode : 3585501029820
- Packaging : Box of 100 items.
64 boxes per pallet.

INSTRUCTIONS FOR USE

Install furring connector between two furrings.

- 1.2.3. The hollow slab hangers are inserted between two concrete slabs using a hammer.



1.

2.

- 4.5. Attach the furring directly to the slab hanger.



3.

4.

6. Secure a short or long SEMIN hanger with (with RHST screws) on the slab hanger and attach the furring to the short or long hanger.



5.

6.

DO YOU KNOW THE ASSOCIATED SEMIN PRODUCTS ?

- Furrings : to fix to hollow slab hangers or to long or short SEMIN hangers
- Hangers : screw to the hollow slab hanger
- RHST screws : to secure the SEMIN hanger to the hollow slab